



PRODUCT TECHNICAL DATA SHEET

Cap FI-52

BASIC DATA

Thread Standards:	Fi 52M	Application:	industrial chemistry
Material Options:	HDPE		household chemistry

DIMENSIONS

Colors:	white, blue, black, green, other to be agreed with our employee	Parameter	Value	Notes
		Diameter:	72 mm	±0,6 mm
		Thread Diameter:	52 mm	±0,4 mm
		Height:	32,6 mm	mm
		Tightening Torque:	5-7 Nm	

PALLETIZATION AND STORAGE - EMPTY PACKAGES

Packaging System No.:	sK360P7200	Pallet:	1200x800 mm
Label Content:	manufacturer's name, production date	Cardboard boxes:	580x380x290
	product type, product quantity (pcs)	Pallet Module:	20 layers, stretch film
	batch number, quality mark	Quantity per layer:	360 pcs
Storage:	protect against sunlight and weather conditions	Quantity per pallet:	7200 pcs
	min. 1m away from heat sources	Pallet Weight:	160 kg
	ambient temperature up to 40°C	Pallet Height:	1,65 m
Shelf Life:	12 months from delivery		

TRANSPORT - EMPTY PACKAGES

Transport:	protection against rain, deformation, contamination and shifting
Warning:	additional loading of transport modules is not permitted
Layer Arrangement:	



STORAGE AND TRANSPORT - FILLED PACKAGING

Completing:	The packaging manufacturer recommends stacking filled canisters in a maximum of three layers, using cardboard dividers on each layer. Completed filled canisters should be wrapped in stretch foil.
Storage:	in covered rooms, on flat surfaces / shelves
	temperature $\leq 40^{\circ}\text{C}$, stacking pallet units is not recommended
	protect against sun and weather conditions, keep a distance of at least 1 m from heat sources
Transport::	stacking pallet units is not recommended
	protection against precipitation, deformation, dirt and movement

ADDITIONAL INFORMATION

- The obligation to validate and confirm the compatibility of the product in the technological process, the logistics chain and in terms of compliance with the filled medium rests with the recipient.

Edition: 2

Modification Date: 10.04.2026